

Data sheet

valid from: 10/1/26







ELGEF Plus Pressure tapping valve PE100
d63-250mm / SDR11 / With 360° rotatable outlet

- 10 bar Gas / 16 bar Water
- With integrated drill bit to tap live mains under pressure
- Complete with lower part and premounted PE100 coated valve piece
- The valve is closed clockwise
- Number of turns to fully open or close valve is 13 for outlet d32
- Number of turns to fully open or close valve is 29 for outlet d63
- Spindle size (SLW) 14
- 4 mm pin connectors
- Limited path fusion indicators
- Long fusion outlet
- Outlet d32 (Do3): Suitable for pipe wall thickness 6.5mm - 23mm
- Outlet d63 (Do3): Suitable for pipe wall thickness 6.5mm - 28mm

d (mm)	Do3 (mm)	DN (mm)	PN (bar)	Code	Weight (kg)	L (mm)	L4 (mm)	Db (mm)	W (mm)	H (mm)	H4 (mm)	Suitable for
63	32	50	16	**193 155 234**	1.811	127	70	21	164	202	97	SDR 9-11
63	63	50	16	**193 155 237**	2.680	160	100	31	164	272	112	SDR 9-11
75	32	65	16	**193 155 244**	1.943	127	70	21	164	208	103	SDR 9-11
75	63	65	16	**193 155 247**	2.749	160	100	31	164	278	118	SDR 9-11
90	32	80	16	**193 155 254**	1.894	127	70	21	164	216	111	SDR 9-11
90	63	80	16	**193 155 257**	2.781	160	100	31	164	286	126	SDR 9-11
110	32	100	16	**193 155 264**	1.896	127	70	21	164	226	121	SDR 9-17.6
110	63	100	16	**193 155 267**	2.739	160	100	31	164	296	136	SDR 9-17.6
125	32	100	16	**193 155 274**	1.986	127	70	21	164	233	128	SDR 9-17.6
125	63	100	16	**193 155 277**	2.867	160	100	31	164	303	143	SDR 9-17.6
140	32	125	16	**193 155 284**	2.009	127	70	21	164	241	136	SDR 9-17.6
140	63	125	16	**193 155 287**	2.908	160	100	31	164	311	151	SDR 9-17.6
160	32	150	16	**193 155 294**	2.029	127	70	21	164	251	146	SDR 9-17.6
160	63	150	16	**193 155 297**	2.913	160	100	31	164	321	161	SDR 9-17.6
180	32	150	16	**193 155 304**	2.111	127	70	21	164	261	156	SDR 9-26
180	63	150	16	**193 155 307**	2.923	160	100	31	164	331	171	SDR 9-26
200	32	200	16	**193 155 314**	2.127	127	70	21	164	271	166	SDR 9-26
200	63	200	16	**193 155 317**	2.980	160	100	31	164	341	181	SDR 9-26
225	32	200	16	**193 155 324**	2.091	127	70	21	164	281	178	SDR 11-26
225	63	200	16	**193 155 327**	2.932	160	100	31	164	353	193	SDR 11-26
250	63	250	16	**193 155 337**	2.978	160	100	31	165	366	206	SDR 11-26

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: http://www.gfps.com